



Hearing Loop Driver



CONTACTA LARGE AREA LOOP SYSTEMS

The V7 is a highly efficient and compact hearing loop driver. It's a constant current perimeter hearing loop driver, suitable for smaller sized venues.

The driver has a Class-D output stage and an audio subsystem built around an advanced Digital Signal Processing (DSP) core. Combined with a powerful CPU to ensure peak performance, the V7 uses cutting edge technology to achieve first-class speech and music reproduction.

Features

- › DSP Controlled Automatic Gain Control (AGC) and High Frequency Compensation for metal loss.
- › Integrated protection circuits with temperature, voltage, short circuit and DC detection
- › Class-D output stage capable of delivering $5A_{RMS}$ @ $7V_{RMS}$
- › Energy efficient design
- › Sleep mode
- › True constant current output stage
- › Continuous self-testing
- › Simple user interface
- › Compact half-width 1RU chassis

Applications

- › Meeting Rooms
- › Classrooms
- › Reception & Waiting Areas
- › Retirement Homes

Voltage and Current

- › $7V_{RMS}$ @ $5A_{RMS}$

contacta 

Phone: (616) 392-3400
Email: sales@contactainc.com
www.contactainc.com

Physical Data

Dimensions	Height - 1.65" Width - 7.80" Depth - 5.90" including control dial
Weight	2.06 lbs
Construction	Mild Steel
Finish	Black Powder Coated

Accessories

- › Rackmount Shelf/Ears/Wall Mount
- › Flat Copper Wire
- › RX20 Loop Listener
- › Field Strength Meter (FSM)

Standards

- › BS EN 55103-1: 2009 (EMC emissions)
- › BS EN 55103-2: 2009 (EMC immunity)
- › FCC class "B" (EMC emissions)
- › ICES-003
- › UL Canada and US Power Supply using less than 100 watts

Technical Data

Power	30W 14Vdc 2.14A External PSU (PS-55) Class 6 External PSU (100V - 240V AC 50Hz - 60Hz)	
Inputs	1 X Line XLR or 3.81mm Euro-block [optimized for levels above -10dBV to 0dBV]	
	1 X Mic Level (12V phantom power via 680 Ohms [optimized for levels above -45dBV])	
	1 X DC Input	
Loop Output Characteristics	Output Voltage	7.5Vrms (21.21Vpk-pk) @ 5A _{RMS} (14.14Vpk-pk)*
	Output Current	5Arms (14.14Vpk-pk) up to 300 seconds*
	Loop Connector	5.08mm Euro-block
Audio System	Frequency Response	80Hz to 6.5kHz
	Distortion	THD+N <1% (-40dB) Full current both outputs driven
	AGC	Peak detecting
	HF Comp	7 optimized stages
Display & Control	Display	LED Backlit LCD display
	Control	Single rotary control
Fault Monitoring and Protection	Main Display	Open circuit loop (DCR measurement)
		Loop ground fault
	Front Panel LED	Output voltage clipping
	Cooling	Internal heatsinks with thermal protection

* Note 1: Z=1.4 Ohms (133uH + 1.37 Ohms @ 0.685kHz) Note 2: <1% (-40dB distortion)